

celer.conf

```
#####  
rpcuser=introduce any name of rpcuser as you want, for example, viggo  
rpcpassword=introduce any password as you want, for example, x  
rpcallowip=127.0.0.1  
rpcport=7777  
port=13737  
#(0=off, 1=on) daemon - run in the background as a daemon and accept commands  
daemon=1  
#(0=off, 1=on) server - accept command line and JSON-RPC commands  
server=1  
listen=1  
txindex=1  
gen=0  
genproclimit=-1  
maxconnections=500  
addnode=185.246.153.155:13737  
addnode=194.182.64.163:13737  
addnode=194.182.84.55:13737  
addnode=199.247.27.175:13737  
addnode=207.148.93.45:13737  
addnode=209.250.243.39:13737  
addnode=45.76.215.51:13737  
addnode=45.77.231.76:13737  
addnode=80.211.66.183:13737  
addnode=80.211.66.238:13737  
addnode=172.125.28.15:13737  
addnode=185.246.153.155:64186  
addnode=194.182.64.163:13737  
addnode=194.182.84.55:13737  
addnode=194.182.84.55:51210  
addnode=199.247.27.175:13737  
addnode=207.148.93.45:13737  
addnode=207.148.93.45:42922  
addnode=209.250.243.39:13737  
addnode=213.183.59.188:13737  
addnode=96.42.30.122:13737  
addnode=212.237.55.96:13737  
#####
```